

Basic Data Storage Systems

Transported good : _____

Surface : _____

Apparent density : ca. _____ kg/qm

Storage capacity _____ boards / stacks of a ø - size (L x W x T) _____ X _____ X _____ mm

Dimension length from _____ to _____ mm

width from _____ to _____ mm

thickness from _____ to _____ mm

Carrier with : single board transportation stack transportation both

fully automatic manual

Transport : without pallet with EURO pallet with base board

own design with dimension (L x W x T): _____ X _____ X _____ mm

Please enclose a sketch of the own design pallet

Stack height : max. _____ mm (with base board and / or pallet)

Stack weight : max. _____ kg **single board weight** : max. _____ kg

Performance : max. _____ single boards/shift.

max. _____ stacks/shift.

Shift : shift period _____ minutes how many shifts per day _____

Sketch of the line arrangement. Position of the in- and outfeed stations with possible connections to existing working machines.

Sketch of the existing place proportions

with the dimension (L x W x H) : _____ X _____ X _____ m

Door opening for transportation of the equipment (W x H): _____ X _____ m

Hall height with lower level of roof beam: _____ mm (pay attention to the roof slope)

Seismic zone: The seismic zone is important for the design of the rack structure, which has a significant influence on the price. Please inform us about the earthquake zone and the ground class of the later installation site.

Number of terminals _____